



**Fixed Focus Versions also
available: 14° | 19° | 26° | 36° | 50°**

Hi-Precision MK2
300W LED RGBW COB
15°-30° | 25°-50°

Hi-Precision 300W LED MK2

RGBW COB LED | 15°-30° | 25°-50°

The device has been specially designed for studio and theater applications where high-definition lighting is a must.

A homogeneous illumination, high light output, stable color temperatures and a high color rendering index characterize this profile. Also the devices are fully flickerfree and the light output with the 300W LED is remarkable. The high-quality LED chip guarantees a long LED life.

Housing made of high-quality flame retardant plastics, XLR 3pin and 5pin DMX connectors, 4 pieces of shutters, goboholder and filterframe are in the scope of delivery.

Hi-Precision 300W LED MK2 | 15°-30° Code 18473 | 25°-50° Code 18475



AC100-240V±10%, 60Hz available



15°-30° or 25°-50°



300W COB RGBW



IP20



917 x 294 x 525 mm



13 kg

SPECIFICATIONS

- » Power Consumption: 320W max
- » Control Channels: 4/6/12
- » Control Signal: DMX512, Auto Mode, Master/Slave Mode
- » Strobe: variable strobing 0-20 flashes per second
- » Illumination intensity: 913LUX / 15M / 15°
- » Luminous flux: 13000lm
- » CRI: Ra>90
- » dimmer: 0-100% linear adjustment
- » working temperature: -20° ~ 40°
- » material: flame retardant plastics
- » Input signal: XLR 3/5-pin(In & Out)
- » Ethernet interface: Aviation plug
- » Power Supply: AC100-240V±10%, 60Hz available
- » Noise: 35dB
- » Case Material: Die Casting Aluminum / Aluminum / Plastic
- » Application: TV Station, TV Studio, Theatre, Stage, Meeting Rooms, Mult Function Rooms, Clubs etc.

LTH - Das Lichttechnikhaus Vertriebs GmbH

Rudolf-Diesel-Str. 3
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0
Fax +49(0)82 21-20 79 8-69

Web www.lth-gmbh.de
E-Mail info@lth-gmbh.de