

Power Flood 30 IP 65

- < 120°
- AC 85-265V 50-60 Hz
- 30W LED
- 225 x 185 x 125 mm
- IP 65
- 2,3kg



Vorteile

- »» 30 Watt HighPower LED
- »» Warmweiß: 2500-3500K / Kaltweiß: 7000-9000K
- »» LED Lebensdauer: 50.000 h
- »» Lichtstrom: 3000 lm
- »» Lichtstärke: 100-110 lm/w
- »» Stromanschluss: AC 85-265V 50-60 Hz
- »» inklusive LED
- »» inklusive Treiber

Beschreibung

Der neue Kapego LED Power Flood 30 ist aus einem massiven Metallgehäuse gefertigt. Als Lichtquelle wurde eine einzelne leistungsstarke LED-Platine mit 30W Leistung verbaut. Die empfohlene Betriebstemperatur liegt zwischen -20 ° C und + 40 ° C (-4°F - + 104°F). Das Gerät erfüllt die Anforderungen der Schutzklasse IP65. Es gibt keinerlei Verzögerung beim Starten der LED. Über den Bügel kann das Gerät in jedem Winkel positioniert werden.

Features

- »» 30 Watt Highpower LED
- »» warmwhite: 2500-3500k/ cool white: 7000-9000k
- »» LED Lifetime: 50.000 hours
- »» Luminous Flux: 3000 lm
- »» Luminous intensity: 100-110 lm/w
- »» Input Voltage: AC 85-264V 50-60 Hz
- »» inclusive LED
- »» inclusive driver

Description

The new Kapego LED Power Flood 30 is equipped with a 30 Watt high Power LED, in a solid metal housing. Operating Temperature range between -20°C +40°C (-4 °F ~+104 °F). Uses a single Powerful LED (30W) for the light source. The LED is closely connected to the crust. Meet the requirement of IP65. No delay start, No waiting. It is safe and removable, and it can be positioned at any angle.