



# Power Flood RGB Series

## Power Flood RGB Series

The popular Power Flood family has now been extended by RGB models! There are several models available: From 60W up to 240W - color changing and dimming can be controlled via DMX.

All models are made from solid metal housing. The light source is a high-performance LED board with 60W, 120W or 240W total output. The recommended operating temperature is between  $-40^{\circ}\text{C}$  and  $+55^{\circ}\text{C}$ . The device meets the requirements of protection class IP 65. To integrate the devices into existing networks with individual DMX start address, please use the optional LTH PRO.fessional DMX start-address programmer.

### Technical Data:

- » Luminous: red 30-40lm/w, green 70- 80lm/w, blue 20-30lm/w
- » available in RF or DMX controll
- » Lifetime: 50.000h
- » CRI (Ra>): 80
- » Working Temperature:  $-40^{\circ} - 55^{\circ}$



120°



High Power LED



IP65



100-240V



2,3 - 9,5 kg



### LTH - Das Lichttechnikhaus Vertriebs GmbH

Rudolf-Diesel-Str. 3  
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0  
Fax +49(0)82 21-20 79 8-69

Web [www.lth-gmbh.de](http://www.lth-gmbh.de)  
E-Mail [info@lth-gmbh.de](mailto:info@lth-gmbh.de)