

# **MSR**

### MSR 575/2 10H 1CT

MSR – bright vivid colors, alwaysThe high color rendering index of the single ended MSR series ensures that everyone in the audience can enjoy the true colors of the scenery, the stage props, the players and their costumes – in fact everything that is on stage can be made bright and vivid in daylight quality light. Also, thanks to the single ended lamp concept, the luminaire has optimal light collection and direction possibilities to help ensure brightness on stage exactly where and when it is needed. In addition, the MSR can be used in any burning position for easy set-up and convenience.

## Product data

#### • Product Data

Product number 245282 MSR 575/2 10H 1CT Full product name MSR 575/2 10H 1CT/4 Short product name Pieces per Sku eop\_pck\_cfg Skus/Case Bar code on pack 8711500198990 8711500199003 Bar code on case 928171605108 Logistics code(s) eop\_net\_weight\_pp 0.055 kg

#### • General Characteristics

System Description Cold Strike
Cap-Base GX9.5
Cap-Base Information
Execution Operating Position
Main Application Studio/Disco
Life to 50% failures EM

Cold Strike
GX9.5
20mm
any
Studio/Disco
1000 hr

### • Electrical Characteristics

Watts 575 W
Lamp Wattage Technical
Lamp Current 6.95 A
Ignition Supply Voltage
Dimmable No

## • Light Technical Characteristics

Color Code Color Rendering 70 Ra8 Index Color Temperature 7200 K 6990 K Color Temperature **Technical** Chromaticity Coor-302 dinate X 320 -Chromaticity Coordinate Y Luminous Flux Lamp 39000 (min), 49000 (nom) Lm Luminous Efficacy 85 Lm/W Lamp EM

#### • Product Dimensions

Overall Length C

Diameter D

Width F

Light Center Length

L

25 mm

30 mm

34 (min), 35 (nom), 36 (max) mm

64 (min), 65 (nom), 66 (max) mm


Arc Length O 7.0 mm

## • Luminaire Design Requirements

Pinch Temperature 350 C Bulb Temperature 700 C



## Dimensional drawing



## GX9.5

Product	A (Min)	A (Nom)	A (Max)	C (Max)	D (Max)	D1 (Norm)	F (Min)	F (Norm)	F (Max)	L (Min)	L (Norm)	L (Max)	O (Norm)
MSR 575/2 10H	-	-	-	125	30	-	34	35	36	64	65	66	7.0



 $\ensuremath{\textcircled{@}}$  2010 Koninklijke Philips Electronics N.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips Electronics N.V. or their respective owners.