



Product Service

# CERTIFICATE

No. B 10 09 25461 011

**Holder of Certificate:** **Kupo Co. Ltd.**

Chung Shin Rd., San Chung  
6F, No.4, Lane 609, Sec. 5  
105 Taipei  
TAIWAN

**Production Facility(ies):** 65382

**Certification Mark:**



**Product:** **Tube coupling  
Coupler for 2" tubes**

**Model(s):** **KCP-820, KCP-830, KCP-832,  
KCP-833, KCP-831, KCP-810,  
KCP-828, KCP-844, KCP-901**

**Parameters:**

Model:	KCP-820
Type:	swivel coupler
Max. load	
Radial direction:	300 kg
Axial direction:	60 kg
Own weight:	0,70 kg
Clamp body	
Dimension:	122 x 120 x 30 mm
Material:	EN AW 6061 T6
Further model and parameter see attachment.	

**Tested according to:** DIN 15560-24:1996  
DIN 15560-25:1987  
DIN 15560-26:1987  
BGV C1:1998

The product was tested on a voluntary basis and complies with the essential requirements. The certification mark shown above can be affixed on the product. It is not permitted to alter the certification mark in any way. In addition the certification holder must not transfer the certificate to third parties. See also notes overleaf.

**Test report no.:** 028-71372228-001

**Date,** 2010-09-28 (Martin Schmied)

Page 1 of 4

TÜV SÜD Product Service GmbH  
Zertifizierstelle  
Ridlerstr. 65 · 80339 München  
Germany



*Martin Schmied*



DEUTSCHES  
AKKREDITIERUNGSSYSTEM  
PRÜFWESEN GMBH



DAP-ZE-1213.00



Models and parameters

Model: **KCP-830**  
 Type: half coupler  
 Max. load  
 Radial direction: 300 kg  
 Axial direction: 60 kg  
 Own weight: 0,30 kg

Clamp body  
 Dimension: 110 x 60 x 30 mm  
 Material: EN AW 6061 T6

Model: **KCP-832**  
 Type: swivel coupler  
 Max. load  
 Radial direction: 500 kg  
 Axial direction: 60 kg  
 Own weight: 1,20 kg

Clamp body  
 Dimensions: 120 x 109 x 50 mm  
 Material: EN AW 6061 T6

Model: **KCP-833**  
 Type: eye ring coupler  
 Max. load  
 Radial direction: 500 kg  
 Axial direction: 60 kg  
 Own weight: 0,65 kg

Clamp body  
 Dimensions: 109 x 60 x 50 mm  
 Material: EN AW 6061 T6





Models and parameters

Model: **KCP-831**  
 Type: half coupler  
 Max. load  
 Radial direction: 500 kg  
 Axial direction: 60 kg  
 Own weight 0,55 kg

Clamp body  
 Dimensions: 109 x 60 x 50 mm  
 Material: EN AW 6061 T6

Model: **KCP-810**  
 Type: arch coupler  
 Max. load  
 Radial direction: 150 kg  
 Axial direction: 30 kg  
 Own weight 0,68 kg

Clamp body  
 Dimensions: 170 x 140 x 40 mm  
 Material: ADC-10

Model: **KCP-828**  
 Type: handcuff coupler  
 Max. load  
 Radial direction: 100 kg  
 Axial direction: 20 kg  
 Own weight 0,45 kg

Clamp body  
 Dimensions: 120 x 105 x 25 mm  
 Material: EN AW 6061 T6





Models and parameters

Model: **KCP-844**  
 Type: TV coupler  
 Max. load  
 Radial direction: 300 kg  
 Axial direction: 60 kg  
 Own weight: 0,90 kg

Clamp body  
 Dimensions: 115 x 106 x 64 mm  
 Material: ADC-12

Model: **KCP-901**  
 Type: Burger coupler  
 Max. load  
 Radial direction: 75 kg  
 Axial direction: 15 kg  
 Own weight: 0,20 kg

Clamp body  
 Dimensions: 112 x 100 x 30 mm  
 Material: EN AW 6061 T6

Munich, 2010-09-28

Martin Schmied

