



Technical Data

Superpanel Full Color 60

Technical features

| | |
|---|----------------------------------|
| Dimensions | 65 cm x 34 cm x 11 cm |
| Weight | 9 kg |
| CRI (Colour Rendering Index) | > 94, typical 96 |
| Dimmer 0 – 100 | included |
| Dimming curves mode | Linear, Exponential, Logarithmic |
| DMX module | included |
| DMX (bit) | 8 bit and 16 bit |
| Connection for 14.8 V battery with standard XLR 4 pin connector | included |
| Standard XLR 5 pin connectors for connection to DMX console | included |
| Watt consumption | 400 W |
| Colour temperature | 2800 K – 10000 K |
| Voltage AC | 90 V – 240 V |
| Frecuency (input) | 50/60 Hz |
| Compliance | CE |

Photometric data

| Distance | 5600 K | 3200 K |
|------------|--------|--------|
| Lux at 1 m | 8,500 | 7,600 |
| Lux at 2 m | 2,400 | 2,300 |
| Lux at 3 m | 1,250 | 1,180 |
| Lux at 4 m | 790 | 760 |
| Lux at 5 m | 590 | 560 |

Mode options

CCT (Correlated Color Temperature)

Mode for variable color temperature control from 2700K to 10000K with the addition of plus and minus green/magenta offset.

HSI (Hue, Saturation and Intensity)

Mode for full-color control.

RGBW

Mode for control of Red, Green, Blue and White independently.

Preset

Mode for a selected variety of gels.

Special Effects

Include Strobe – Party – Copcar – Disco.
