

 Squareled



**Royal Flash 3000**

**LED Strobe Light**

**LTH**   
Das Lichttechnikhaus Vertriebs GmbH

# Royal Flash 3000 LED Strobe Light

- » Squared Royal Flash 3000 LED Strobe Light
- » Light source: 228x3W white LEDs (Strobe)  
+64x 0.3w RGB LEDs (backlight) array
- » Minimum LED lifetime: 50 000 hours
- » Resolution: 8 bits per color plus 8-bit dimming
- » Control systems: DMX
- » DMX channels: 3/4/14 Channels
- » Setting: Control panel with backlit monochrome display

## Royal Flash 3000 LED Strobe Light | Code 18469



228 x 3 W (white) + 64x 0,2 W RGB LEDs



550W



500 x 340 x 240 mm



7 kg



IP20

## SPECIFICATIONS

- » Strobe: 0.289 - 16.667 Hz, variable flash rate, intensity and duration
- » Special effects: Blinder, ramp up/down, random flash, lightning, spikes, pre-programmed FX
- » Aura (secondary LED array illumination) color mixing: RGB
- » Beam (strobe) array Light source: 228pcs x 3W white color LED
- » Resolution: 8-bit Dimming, above 16.7% output intensity: Current-controlled, flicker-free
- » Dimming, below 16.7% output intensity: PWM (refresh rate 6000 Hz)
- » Minimum LED lifetime: 50 000 hours
- » Aura (backlight) array
- » Light source: 64pcs x 0.8W RGB LEDs
- » Resolution: 8 bits per color plus 8-bit dimming
- » Dimming: PWM (refresh rate 1001 Hz)
- » Minimum LED lifetime: 50 000 hours
- » AC power: Neutrik PowerCON TRUE1 male socket
- » DMX data in/out: 5-pin locking XLR
- » Atomic Colors color gel scroller: 4-pin locking XLR

## LTH - Das Lichttechnikhaus Vertriebs GmbH

Rudolf-Diesel-Str. 3  
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0  
Fax +49(0)82 21-20 79 8-69

Web [www.lth-gmbh.de](http://www.lth-gmbh.de)  
E-Mail [info@lth-gmbh.de](mailto:info@lth-gmbh.de)