
# Squareled





## **CAPRICE 19x40W RGBW**

**WASH ZOOM with Pixel Control** 



### **CAPRICE 19x40W**

#### **RGBW WASH ZOOM** with Pixel Control

SquareLED CAPRICE comes with a smooth, fast and quiet motorized zoom from 6°-60°.

It features 19\*40W 4-in-1 RGBW LUMINUS leds with pixel control.

The SquareLED CAPRICE LED wash light is a flicker-free fixture with even, soft edge and pure color mixing coverage.

It provides internal programs, virtual colors, dynamic patterns, static patterns and kinds of pre-programming linear color temperature adjustment options.

#### CAPRICE 19x40W RGBW | Code 18546













23,5kg

810W

AC90-260V 50/60Hz

>>

sound activated or auto operation Control Channel: 20/14/92/98 DMX channels IISITT DMX-512

**SPECIFICATIONS** Life span: 50000 hours life span

Control Signal: DMX512 master-slave and

- 8/16 Bit smooth, fast and precise PAN/TILT movement (3-phase motor)
- 630°/540°/360°PAN optional and 270°/180°/90°TILT optional
- PAN/TILT reversible advantage
- PAN/TILT calibration available >>
- pixel each color and each led controllable individually
- Color temperature Liner up and down in 2,800-8,000K
- Even, soft edge and pure color mixing coverage
- Using the three phase motor provide high speed and smooth scan and eliminate the rotational noise

- Flicker free sources management
- Scan position memory, auto reposition after unexpected movement
- 0-100% Smooth linear LED dimmer
- 7 built-in default programs for easy operation
- Different Kinds of pre-programmed macro effects with variable speed
- Variable speed strobe effect with 1-25 flashes per second
- Variable pusle and random effects
- Sound control with sensitivity adjustment
- Efficient low noise self adjusting fan cooling system
- Constant temperature readout and management function
- Over heat protection management
- Power con IN/OUT with power switch and fuse
- 3-Pin DMX connectors IN/OUT
- DB rating@1M=54.18dB

#### ITH - Das Lichttechnikhaus Vertriehs GmbH

Rudolf-Diesel-Str. 3 D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0 +49(0)82 21-20 79 8-69 Fax

Web F-Mail

www.lth-gmbh.de info@lth-gmbh.de