


**Squareled**



15° Illumination(LUX)	R:	5907	993	374	252	118
	G:	4953	1394	378	289	181
	B:	1292	407	183	118	58
	A:	12259	4677	1881	1170	553
	L:	11022	4056	1553	1018	435

30° Illumination(LUX)	R:	1876	296	120	63	45
	G:	1545	399	182	96	67
	B:	880	125	58	30	22
	A:	8865	1228	578	298	214
	L:	4191	1072	493	261	184



**Hi-Precision 500W**  
**RGBAL LED 15°-30° | 25°-50°**

**LTH**  
 Das Lichttechnikhaus Vertriebs GmbH

# Hi-Precision 500W

## RGBAL LED 15°-30° | 25°-50°

The device has been specially designed for studio and theater applications where high-definition lighting is a must. A homogeneous illumination, high light output, stable color temperatures and a high color rendering index characterize this profile.

Also the devices are fully flickerfree and the light output with the 500W LED is remarkable. The high-quality LED chip guarantees a long LED life.

Housing made of high-quality flame retardant plastics, XLR 3pin and 5pin DMX connectors, 4 pieces of shutter, goboholder and filterframe are in the scope of delivery.

Also available with fixed focus tubus: 14° / 19° / 26° / 36° / 50°

Hi-Precision 500W RGBAL LED 15°-30° | Code 18516

Hi-Precision 500W RGBAL LED 25°-50° | Code 18517



500W COB RGBAL



500W



15° - 30° or 25°-50°



IP20



768 × 285 × 525mm



11,5kg (netto)

## SPECIFICATIONS

- » Control Channels: 4/6/12
- » Control Signal: DMX512, Auto Mode, Master/Slave Mode
- » Strobe: variable strobing 0-20 flashes per second
- » Illumination intensity:  
8M / 15° = R252 G380 B116 A1170 L1018
- » Luminous flux: 19000lm
- » dimmer: 0-100% linear adjustment
- » CRI: Ra > 90
- » working temperature: -20° ~ 40°
- » material: flame retardant plastics
- » Input signal: XLR 3/5-pin (In & Out)
- » Ethernet interface: Avaiation plug
- » Power Supply: AC100-240V 50/60HZ
- » very silent: < 35dB
- » Case Material: Die Casting Aluminum / Aluminum / Plastic
- » Application:  
TV Station, TV Studio, Theatre, Stage, Meeting Rooms, Multi Function Rooms, Clubs etc.

## LTH - Das Lichttechnikhaus Vertriebs GmbH

Rudolf-Diesel-Str. 3  
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0  
Fax +49(0)82 21-20 79 8-69

Web [www.lth-gmbh.de](http://www.lth-gmbh.de)  
E-Mail [info@lth-gmbh.de](mailto:info@lth-gmbh.de)