

**S**quareled



**Neptune 300W**  
COB Fresnel IP65 WW | CW

**LTH**   
Das Lichttechnikhaus Vertriebs GmbH

# Neptune 300W

## COB Fresnel IP65 WW | CW

Now finally with IP65 protection class and thus suitable for outdoor use: Classical stagelighting by Fresnel lens luminaire and 300W light output. The barndoor is in the scope of delivery. Installed in the direction of the audience, the device also acts as a blinder with a 29 ° beam angle, thereby offering a further possible use.

The SquareLED Neptune is available in two color temperatures: 3200K or 5600K.



### SPECIFICATIONS

- » Voltage: AC100-240V,50-60/HZ
- » Dimming:0~100% linear dimming
- » Dimmer rate: 16K
- » Control Mode: DMX512/masterslave/automatic/manual mode
- » Display screen: LCD screen
- » Push button: Touch glass button
- » DMX: 1/2/3CH
- » Color temperature: 3200K or 5600K
- » DMX channels: 1/2/3 CH
- » control: DMX512/masterslave/automatic/manual mode
- » power connection: 3pin plug IP65
- » data connection: 3pin plug IP65

**Neptune 300W COB Fresnel IP65 WW | Code 18481**

**Neptune 300W COB Fresnel IP65 CW | Code 18482**



LED WW or CW 300W COB light bulb



300W



29°



IP65



340 × 410 × 200mm



9.7kg

**LTH - Das Lichttechnikhaus Vertriebs GmbH**

Rudolf-Diesel-Str. 3  
D-89312 Günzburg

Phone +49 (0)82 21-20 79 8-0  
Fax +49(0)82 21-20 79 8-69

Web [www.lth-gmbh.de](http://www.lth-gmbh.de)  
E-Mail [info@lth-gmbh.de](mailto:info@lth-gmbh.de)