

Studio Due®

emotion and creativity in light



[Optional]

- Barndoor
- Wireless DMX receiver

- Compact form factor and robust aluminium case
- IP 67 flood light projector


Smart max30

SMART MAX30 RDM WB and M (White Balance and Monochromatic) is our new floodlight projector with compact design and robust aluminium case suitable for accent lighting. DMX RDM or Plug-in version. IP67 rating protection.

Fixture colour finishing is grey.

| ITEM | FIXTURE | [KEY features] SMART MAX30 |
|-------------------|---------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LEDs | Monochromatic | 30 NICHIA-NVSL219C 4000K available 2700K, 5000K, 6500K On request: red, green, blue or amber |
| | White Balance | 15 warm white (2700K) + 15 cool white (6500K) NICHIA-NVSL219C |
| Total light power | | 40W |
| Lumen | Monochromatic | 5000lm @4000K |
| | White Balance | 4500lm @4000K |
| Optics | | 24° (23mm lenses) PMMA 8N - On request: 12°, 36°, 10°x30°, 15°x55° |
| Tilt | | 175° manual |
| Connections | | IN-OUT DMX 3pins IP67 connectors (none for Plug-in version) - 1.5mt 3x1 cable with bare ends |
| Control - Setup | | DMX 512 / RDM - RDM / DRS Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Halogen simulation Flicker-free function Smooth dimming function |
| Power consumption | | 44W - 0,2A@230V |
| Voltage range | | Universal 100/240VAC, 47-63Hz, Active PFC: >0.9@230V |
| DMX channels | | Monochromatic : 3CH mode, 1CH mode - White Balance: 4CH mode, 2CH mode, 1CH mode (none for Plug-in version) |
| Physical | | 205x110x235 mm |
| Weight | | 3,2 Kg |
| Material | | Housing in die-cast aluminium - bracket in stainless steel - ultra clear white 4mm tempered glass |

art. 2052: SMART MAX30 WB / RDM
art. 2053: SMART MAX30 M / RDM
art. 20531: SMART MAX30 M Plug-in



PHYSICAL

www.studiodue.com

