



Studio Due®

emotion and creativity in light



Refined and compact, IP67, SINGLE 40 RGBW/FC (Full Color) is a LED Lighting fixture with a large and uniform light output. High brightness LEDs RGBW/FC, combines an innovative optic system with a wide beam and a superb color mixing. Highly efficient and impressive light output. Suitable for permanent architectural installations and for temporarily events.

- Standard fixture colour finishing is black. Optional grey and white (art. FX-COLOUR).

| ITEM | FIXTURE | [KEY features] |
|--|---------|--|
| LEDs | RGBW | n. 40 (5050-20W-RTBH) LEDs |
| Total light power | | 190W |
| Lumen | | Red 3250lm, Green 7500lm, Blue 1200lm, White 7500lm |
| Optics | | 25° (45mm lenses) On request: - 10°, 40° (45 mm lenses) - 65° plan-filter - Barn-door - Anti-glare |
| Housing | | Made in extruded and cast aluminium + steel. Ultraclear 4mm tempered glass. Powder-coated finish. |
| Tilt | | Manual 160° |
| Switching power supply (universal voltage) | | |
| Rated Voltage | | 100-240Vac; 47-63Hz |
| Rated Power | | 210W |
| Rated Current | | 0,9A@230VAC; Fuse T5A |
| PFC | | PF>0.95@230VAC |
| Physical | | WxDxH: 615x185x415 mm |
| Weight | | 19 Kg |
| Rating Protection | | IP67 |
| Control | | Standard interface: RS-485, optocoupled input - Protocol: USITT DMX512 |
| Connections | | Signal: 4pin IP 67 connector (male-female) Main Power: 3x1mm cable 1,5mt Available as accessories: Wireless DMX receiver |
| Setup | | Control panel with touch technology Led display with flip function Dedicated DMX channel for white balance DMX or Auto mode with Master-Slave function Intelligent temperature control Flicker-free function Smooth dimming function Halogen simulation CYM simulation |
| DMX channels | | 9CH mode, 5CH mode, 4CH mode |



PHYSICAL

www.studiodue.com

