

CITYBEAM LED SL84 RGBW (it.177510)



Specifiche tecniche

LED type	RGBW Hi-Power
Number of LEDs	84
Lumen MAX	16600
Red lumen (lm)	3400
Green lumen (lm)	6000
Blu lumen (lm)	33W
White lumen (lm)	7200
Lenses	4° Ultra Narrow 8° 15° 15° x 30° 25° 40° 60°
Connectors and cables	Main Power: 3x1,5mm cable DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	LED display with flip function Dedicated DMX channel for white balance from 2000K to 10000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel

DMX channels	9ch - 5ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	250W
Current	1,1A@230VAC
Power Factor	PF>0,95@230VAC
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	613 x 184 x 415 mm
Weight (Kgs)	18,5 Kg.
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Narrow Beam
Accessories - Flight case	None Yes
Accessories - Anti glare	None Yes
Accessories - Barn door	None Yes

La tua configurazione

LED type	RGBW Hi-Power
Number of LEDs	84
Lumen MAX	16600
Red lumen (lm)	3400
Green lumen (lm)	6000
Blu lumen (lm)	33W
White lumen (lm)	7200
Lenses	4° Ultra Narrow
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	250W
Current	1,1A@230VAC
Power Factor	PF>0,95@230VAC
IP protection rating	IP 67
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	613 x 184 x 415 mm
Weight (Kgs)	18,5 Kg.
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Narrow Beam
Accessories - Flight case	None
Accessories - Anti glare	None
Accessories - Barn door	None

