

CITYCOLOR LED RGBW (it.130210)



Specifiche tecniche

LED type	RGBW5050MULTICHIP
Number of LEDs	120
LED expected lifetime (hrs)	50000
Lumen MAX	55400
Red lumen (lm)	11300
Green lumen (lm)	22000
Blu lumen (lm)	3400
White lumen (lm)	22100
Lenses	8° 15° 15° x 30° standard 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60° frost 65°
Connectors and cables	Main Power: 3x1,5mm cable DMX signal: 4pin IP67 connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	RDM/DRS + touch control panel LED display with flip function Dedicated DMX channel for white balance from 2000K to 10000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + touch control panel
DMX channels	9ch - 5ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	660
Current	2,9A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	40A@230V
Tilt	240° - 2 adjustable heads +9° each
IP protection rating	64
IK grade protection	07
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	680 x 145 x 640
Weight (Kgs)	32
Materials	Ultra clear 4mm tempered glass PMMA lenses Aluminium alloy housing Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Wall Washer
LED 6000K White	None Yes
Accessories - Flight case	None Yes
Accessories - Anti glare	None Yes

Accessories - Barn door	None
	Yes

La tua configurazione

LED type	RGBW5050MULTICHIP
Number of LEDs	120
LED expected lifetime (hrs)	50000
Lumen MAX	55400
Red lumen (lm)	11300
Green lumen (lm)	22000
Blu lumen (lm)	3400
White lumen (lm)	22100
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	660
Current	2,9A@230VAC
Power Factor	PF>0,95@230VAC
Inrush current	40A@230V
Tilt	240° - 2 adjustable heads +9° each
IP protection rating	64
IK grade protection	07
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	680 x 145 x 640
Weight (Kgs)	32
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Wall Washer
LED 6000K White	None
Accessories - Flight case	None
Accessories - Anti glare	None
Accessories - Barn door	None

