

## PARLED 100 RGBW IP20 (it.150610)



### Specifiche tecniche

LED type	RGBW5050MULTICHIP
Number of LEDs	7
LED expected lifetime (hrs)	50000
Lumen MAX	3300
Red lumen (lm)	680
Green lumen (lm)	1300
Blu lumen (lm)	220
White lumen (lm)	1300
Lenses	8° 15° 15° x 30° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60°
Connectors and cables	Main Power: 3x1,5mm cable DMX signal: XLR5pin connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)

Functions	Dedicated DMX channel for white balance from 2900K to 13000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + push button panel
DMX channels	9ch - 6ch - 5ch - 4ch
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	43
Current	0,2A@230V
Inrush current	35A@230V
Tilt	360°
IP protection rating	IP 20
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	187x140x230
Weight (Kgs)	2 Kg.
Materials	Ultra clear 4mm tempered glass PMMA lenses All aluminium alloy Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Standard Grey
Product Category	Spot
Accessories - Barn door	None Yes

## La tua configurazione

LED type	RGBW5050MULTICHIP
Number of LEDs	7
LED expected lifetime (hrs)	50000
Lumen MAX	3300
Red lumen (lm)	680
Green lumen (lm)	1300
Blu lumen (lm)	220
White lumen (lm)	1300
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	43
Current	0,2A@230V
Inrush current	35A@230V
Tilt	360°
IP protection rating	IP 20
Operating temperature	-30°C +45°C
Sizes l x p x h (mm)	187x140x230
Weight (Kgs)	2 Kg.
Mounting systems	Surface
Colour finishing	Standard Grey
Product Category	Spot
Accessories - Barn door	None