

T-COLOR RGBW (it. 140510)



Specifiche tecniche

LED type	RGBW5050MULTICHIP
Number of LEDs	60
Lumen MAX	34000
Red lumen (lm)	7000
Green lumen (lm)	14000
Blu lumen (lm)	3000
White lumen (lm)	13000
Lenses	8° 10°x30° 15° 25° 40° 60°
Filters	None f 60° f 100° f 8°x 60° frost 65°
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	RDM/DRS + touch control panel Wireless DMX receiver
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	460
IP protection rating	IP 67
Sizes l x p x h (mm)	613 x 184 x 420

Weight (Kgs)	19
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional) Any RAL (optional)
Marine Grade treatment	None Yes
Product Category	Wall Washer

La tua configurazione

LED type	RGBW5050MULTICHIP
Number of LEDs	60
Lumen MAX	34000
Red lumen (lm)	7000
Green lumen (lm)	14000
Blu lumen (lm)	3000
White lumen (lm)	13000
Lenses	8°
Filters	None
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	460
IP protection rating	IP 67
Sizes l x p x h (mm)	613 x 184 x 420
Weight (Kgs)	19
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Wall Washer