

## STADIO 300 RGBWA (it. 176010)



### Specifiche tecniche

LED type	RGBWA
Number of LEDs	36
Lumen MAX	14600
Red lumen (lm)	2200
Green lumen (lm)	5000
Blu lumen (lm)	700
White lumen (lm)	5000
Amber lumen (lm)	2400
Lenses	12° 15° x 30° 15° x 55° 24° 36°
Connectors and cables	Main Power: PowerCon IP65 connector (male-female) DMX signal: XLR5pin connector (male-female)
Control type	Protocol USITT DMX512 - RDM Protocol USITT DMX512 - RDM + Wireless (on request)
Functions	Dedicated DMX channel for white balance from 2000K to 10000K DMX or Auto Mode with Master-Slave function Intelligent temperature control Continuous dimming 0-100% Smooth dimming function Halogen simulation CYM simulation Flicker-free function
Setup	RDM/DRS + push button panel
DMX channels	10ch - 7ch - 6ch - 5ch
Input range	100 - 240 VAC; 47/63 Hz

Power (W)	160
Current	0,7A@230V
Power Factor	PF>0,95@230VAC
Tilt	360°
IP protection rating	IP 20
Sizes l x p x h (mm)	365 x 90 x 265
Weight (Kgs)	6,6
Materials	PMMA lenses Polyester powder coated
Mounting systems	Surface Truss (optional)
Colour finishing	Black RAL 9005 (standard) Grey RAL 9006 (optional) White RAL 9010 (optional)
Marine Grade treatment	None Yes
Product Category	Spot

## La tua configurazione

LED type	RGBWA
Number of LEDs	36
Lumen MAX	14600
Red lumen (lm)	2200
Green lumen (lm)	5000
Blu lumen (lm)	700
White lumen (lm)	5000
Amber lumen (lm)	2400
Lenses	12°
Control type	Protocol USITT DMX512 - RDM
Input range	100 - 240 VAC; 47/63 Hz
Power (W)	160
Current	0,7A@230V
Power Factor	PF>0,95@230VAC
Tilt	360°
IP protection rating	IP 20
Sizes l x p x h (mm)	365 x 90 x 265
Weight (Kgs)	6,6
Mounting systems	Surface
Colour finishing	Black RAL 9005 (standard)
Marine Grade treatment	None
Product Category	Spot