



BEXPO200MCW











Main features

- Safety Eye
- Silent mode
- 16-bit dimming
- Double glass optics
- Manual zoom
- One hand locking
- Adaptable frequency rate
- Holds dim value when powercut
- Color-matched with B Expo100/350

High CRI fresnel

The B Expo200MCW is a high power LED fresnel light specially designed for high demanding customers. It delivers a very powerful and high-quality wash light. The specific feature set and nice design make it the ideal tool for high power applications in exhibitions, museums, shops, and everywhere else where high power quality light is required.

Accessories

- Powercable with bare ends
- Safety chain
- DMX cable
- Optional 12-leaf barn door
- Optional white cover kit

Certifications

- TÜV SÜD GS
- CE & US certified



SPEC SHEET



Optical

Lamp type	LED fresnel
Beam angle	15° - 45°
Colours	5.600K
Refresh rate	Adaptable 600 - 4.000Hz
Strobe	0-20Hz
CRI	94 Ra
TM30	Rf = 90 Rg = 103

Physical

Dimensions (WxHxD)	404 x 320 x 467 mm 15.9 x 12.6 x 18.4 in
Packing dimensions (WxHxD)	439 x 386 x 511 mm 17.3 x 15.2 x 20.1 in
Net weight	10 kg 22.1 lbs
Gross weight	11 kg 24.3 lbs
Cooling	Heat pipe + air cooling

Mounting


Hanging	3x M12 hole
2nd suspension/safety wire	1x eye in back of the unit to pass carabiner

Control


Menu	OLED display with 4 buttons
Control	DMX/RDM, manual
DMX mode	1/4/5 channels
Dimmer mode	16-bit dimming
In/Link	XLR 5-Pin
Zoom	Manual
Movement	One hand tilt locking


Electrical

Fixture rated power	220W
LED engine	200W 5.600K
Input power	240V ~ 50Hz Auto switching power supply
In/Link	powerCONTRUE1 max link current: 10A
IP rating	IP20



404 mm | 15.9 in







SPEC SHEET



Photometric data

